

User Manual

43" PROFESSIONAL MONITOR FOR CCTV BP-MON-43CCTV



(!) Attention

- ·Use only the power cord supplied with this device. If other power lines are used, please ensure that they have passed the national standard certification;
- ·Do not open the display (there is a very dangerous high voltage in the equipment);
- ·To avoid the danger of electric shock, please cut off the power supply during installation. commissioning and moving;
- · Do not install it near the heat source, so as to avoid high product temperature and damage to the product:
- · Do not use the monitor near water, corrosive, flammable and explosive places;
- · Do not use any hard substance to rub or strike the display screen:
- ·Unplug the monitor first, and then clean the screen surface of the monitor;
- · Handle with care during transportation and handling.

Packing list

1、Monitor









5. Product description

Remote control


(* if any of the above items are damaged or missing, please contact the dealer immediately.)

Basic parameters

Display size	3840*2160	
Screen type	TFT-LED	
NTSC	72% (typical)	
Brightness	500 cd/m ²	
Contrast ratio	3000-5000: 1	
power	50W~180W	
Power frequency	AC110V/220V/50Hz/60Hz	

(* Please refer to the actual parameters for different product sizes)

(r) Interface function description diagram



■ Key function description



Α	В	С	D	E	F	G
Volume-	Volume +	up	down	Signal source key	Menu key	On / off key

Operating instructions

- 1. Power on, press the power key to start the machine, and press and hold to shut down the
- 2. Channel selection: press the input key, press the p-/p + key to select the signal channel, and then press the v-/v + key to confirm.
- 3、 Image effect design: press the menu key to enter the menu, press the p-/p + key to select different items, press the V + key, press the V key and the hole section value respectively, and finally press the menu key to exit.
- 4. Four Multimedia: insert the USB flash disk, press the input key to select multimedia, press the v-/v + key to enter the multimedia interface, press the v-/v + key to select left and right, press the p-/p + key to select different items, and then press the input key to confirm.

Base installation guide

- 1. Place the monitor flat on the table, with the bottom facing outward in an outward splay shape;
- 2. Clip the base to the connection on the monitor and tighten the screws clockwise:
 - 3. Adjust the monitor to the best viewing angle.





(* we recommend that you lay a soft cloth on the desktop to avoid damaging the monitor.)

Base Removal Guide

- 1. Place the monitor flat on the table with the bottom facing outward;
- 2. Turn the screw counterclockwise to loosen the connection:
- Pull out the base.





(* we recommend that you lay a soft cloth on the desktop to avoid damaging the monitor.)

For Inquiries, Please contact:

Security Shop Vladimira Popovica 6/6/A606 11070 Novi Beograd, Serbia Tell: +381 11 318 68 68 office@securityshop.rs

Imported/Distributed by Security Shop doo license of Blaupunkt www.blaupunkt.com Made in China